



023040270

LED GU5.3 MR16 PMMC 50x50mm 12V
270Lm 4W 2700K 827 45° AC/DC Niet-Dimbaar

Huishoudelijk, Spot GU5.3 12V Premium



| General | | Energy | | |
|-----------------------------|-------------|-------------------------|----------------|----------------|
| Eprel registration no | 831059 | Operating voltage | 12 V | |
| Socket | GU5.3 | Volt | 12 V | |
| Bulb shape | MR16 | Frequency | 50..60 Hz | |
| Width | 50.00 mm | Watt | 4 W | |
| Depth | 50.00 mm | Current type | AC/DC | |
| Height | 50.00 mm | Power factor | 0.5 | |
| Finish | Clear | Energy efficiency class | G | |
| Colour | Silver | Energy consumption | 4 W | |
| Colour housing | Silver | Lamp efficacy | 67.50 | |
| Body material | Aluminium | LED | | |
| Lifespan | 30000 hours | Filament LED | No | |
| Switches | 50000 | LED type | COB | |
| Beam angle | 45 ° | Dimm type | Non-Dim | |
| Dimmable | No | Number of leds / sticks | 1 | |
| Degree of protection | IP20 | Colour consistency SDCM | SDCM6 | |
| Net weight | 0.031 kg | Dim to warm | No | |
| Warranty | 2 years | Adjustable beam angle | No | |
| Light | | Ordering details | | |
| Kelvin | 2700 K | 023040270 | Quantity pc(s) | EAN |
| Colour temp nr | 827 | Single package | 1 | 8718309825201 |
| Stable lumen | 350 lm | Inner carton | 20 | 18718309825208 |
| Lumen 90 cone | 270 lm | Outer carton | 100 | 28718309825205 |
| Luminous intensity | 500 cd | | | |
| Color Rendering Index (CRI) | 82 | | | |

