



L022940030

LED GU10 MR11 Glas 35x47mm 230V 160Lm
3W 3000K 830 40° AC Helder Dimbaar

Huishoudelijk, Spot GU10 MR11



| General | | Energy | |
|-----------------------|-------------|-------------------------|------------|
| Eprel registration no | 831200 | Operating voltage | 230 V |
| Socket | GU10 | Volt | 220..240 V |
| Bulb shape | MR11 | Frequency | 50..60 Hz |
| Width | 35.00 mm | Watt | 3 W |
| Depth | 35.00 mm | Current type | AC |
| Height | 47.00 mm | Power factor | 0.9 |
| Finish | Clear | Energy efficiency class | G |
| Colour | Silver | Energy consumption | 3 W |
| Colour housing | Silver | Lamp efficacy | 53.33 |
| Body material | Glass | | |
| Lifespan | 30000 hours | | |
| Switches | 15000 | | |
| Beam angle | 40 ° | | |
| Dimmable | Yes | | |
| Degree of protection | IP20 | | |
| Net weight | 0.029 kg | | |
| Warranty | 2 years | | |

| LED | |
|-------------------------|---------------|
| Filament LED | No |
| LED type | SMD |
| Dimm type | Trailing edge |
| Number of leds / sticks | 5 |
| Colour consistency SDCM | SDCM5 |
| Dim to warm | No |
| Adjustable beam angle | No |

| Light | |
|-----------------------------|--------|
| Kelvin | 3000 K |
| Colour temp nr | 830 |
| Stable lumen | 200 lm |
| Lumen 90 cone | 160 lm |
| Luminous intensity | 270 cd |
| Color Rendering Index (CRI) | 82 |

| Ordering details | | |
|------------------|----------------|----------------|
| L022940030 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739060357 |
| Inner carton | 10 | 18718739060354 |
| Outer carton | 100 | 28718739060351 |

| Remark |
|--|
| General note: GU10 glass versions need to cool down after 8 hrs burning (switch off for half an hour), because of limited heat dissipation |

