



## L480301140

LED PLS 2G7 4 pin Glas T37x205mm 230V  
730Lm 5W (PLS11W) 4000K 840 AC Opaal  
Niet-Dimbaar

### Marine & Industrie, PLS 2G7 4pin



General		Energy		
Eprel registration no	1869522	Operating voltage	230 V	
Socket	2G7	Volt	220..240 V	
Bulb shape	T37	Frequency	50..60 Hz	
Width	37.00 mm	Watt	5 W	
Depth	21.00 mm	Current type	AC	
Height	205.00 mm	Power factor	0.5	
Finish	Opal	Energy efficiency class	D	
Colour	White	Energy consumption	5 W	
Colour housing	White	Lamp efficacy	146.00	
Body material	Glass	<b>LED</b>		
Lifespan	25000 hours	Filament LED	No	
Switches	15000	LED type	SMD 2835	
Beam angle	270 °	Dimm type	Non-Dim	
Dimmable	No	Number of leds / sticks	60	
Degree of protection	IP20	Colour consistency SDCM	SDCM6	
Net weight	0.043 kg	Dim to warm	No	
Warranty	2 years	Adjustable beam angle	No	
Light		Ordering details		
Kelvin	4000 K	L480301140	Quantity pc(s)	EAN
Colour temp nr	840	Single package	1	8718739071865
Stable lumen	730 lm	Inner carton	10	18718739071862
Color Rendering Index (CRI)	80	Outer carton	100	28718739071869

