



L480401840

LED PLC G24d 2 pin Glas T34x143mm 230V
880Lm 6W (PLD18W) 4000K 840 AC+CCG
Opaal Niet-Dimbaar

Marine & Industrie, PLC G24d 2pin



General		Energy		
Eprel registration no	2039293	Operating voltage	230 V	
Socket	G24d	Volt	220..240 V	
Bulb shape	T34	Frequency	50..60 Hz	
Width	34.00 mm	Watt	6 W	
Depth	34.00 mm	Current type	AC	
Height	143.00 mm	Power factor	0.9	
Finish	Opal	Energy efficiency class	D	
Colour	White	Energy consumption	6 W	
Colour housing	White	Lamp efficacy	146.67	
Body material	Glass	LED		
Lifespan	30000 hours	Filament LED	No	
Switches	15000	LED type	SMD 2835	
Beam angle	270 °	Dimm type	Non-Dim	
Dimmable	No	Number of leds / sticks	48	
Degree of protection	IP20	Colour consistency SDCM	SDCM6	
Net weight	0.062 kg	Dim to warm	No	
Warranty	2 years	Adjustable beam angle	No	
Light		Ordering details		
Kelvin	4000 K	L480401840	Quantity pc(s)	EAN
Colour temp nr	840	Single package	1	8718739071896
Stable lumen	880 lm	Inner carton	10	18718739071893
Color Rendering Index (CRI)	80	Outer carton	100	28718739071890

