



L480501830

LED PLC G24q 4 pin Glas T34x143mm 230V
850lm 6W (PLDE18W) 3000K 830 AC
Opaal Niet-Dimbaar

Marine & Industrie, PLC G24q 4pin



General		Energy		
Eprel registration no	2039297	Operating voltage	230 V	
Socket	G24q	Volt	220..240 V	
Bulb shape	T34	Frequency	50..60 Hz	
Width	34.00 mm	Watt	6 W	
Depth	34.00 mm	Current type	AC	
Height	143.00 mm	Power factor	0.9	
Finish	Opal	Energy efficiency class	D	
Colour	White	Energy consumption	6 W	
Colour housing	White	Lamp efficacy	141.67	
Body material	Glass	LED		
Lifespan	30000 hours	Filament LED	No	
Switches	15000	LED type	SMD 2835	
Beam angle	270 °	Dimm type	Non-Dim	
Dimmable	No	Number of leds / sticks	48	
Degree of protection	IP20	Colour consistency SDCM	SDCM6	
Net weight	0.062 kg	Dim to warm	No	
Warranty	2 years	Adjustable beam angle	No	
Light		Ordering details		
Kelvin	3000 K	L480501830	Quantity pc(s)	EAN
Colour temp nr	830	Single package	1	8718739071926
Stable lumen	850 lm	Inner carton	10	18718739071923
Color Rendering Index (CRI)	80	Outer carton	100	28718739071920

