



L480603230

LED PLT GX24q 4 pin Glas T49x140mm
230V 1350Lm 10W (PLTE32W) 3000K 830
AC Opaal Niet-Dimbaar

Marine & Industrie, PLT GX24q 4pin



General		Energy		
Eprel registration no	2039302	Operating voltage	230 V	
Socket	GX24q	Volt	220..240 V	
Bulb shape	T49	Frequency	50..60 Hz	
Width	49.00 mm	Watt	10 W	
Depth	45.00 mm	Current type	AC	
Height	140.00 mm	Power factor	0.9	
Finish	Opal	Energy efficiency class	D	
Colour	White	Energy consumption	10 W	
Colour housing	White	Lamp efficacy	135.00	
Body material	Glass	LED		
Lifespan	30000 hours	Filament LED	No	
Switches	15000	LED type	SMD 2835	
Beam angle	270 °	Dimm type	Non-Dim	
Dimmable	No	Number of leds / sticks	72	
Degree of protection	IP20	Colour consistency SDCM	SDCM6	
Net weight	0.094 kg	Dim to warm	No	
Warranty	2 years	Adjustable beam angle	No	
Light		Ordering details		
Kelvin	3000 K	L480603230	Quantity pc(s)	EAN
Colour temp nr	830	Single package	1	8718739072008
Stable lumen	1350 lm	Inner carton	10	18718739072005
Color Rendering Index (CRI)	80	Outer carton	100	28718739072002

