



L642763027-1

LED GU10 MR16 Glas 50x54mm 230V
350Lm 3.7W 2700K 827 36° AC 3 Step
Dimbaar

Huishoudelijk, Spot GU10 Glass



| General | | Energy | |
|-----------------------|-------------|-------------------------|------------|
| Eprel registration no | 2451097 | Operating voltage | 230 V |
| Socket | GU10 | Volt | 220..240 V |
| Bulb shape | MR16 | Frequency | 50..60 Hz |
| Width | 50.00 mm | Watt | 3.7 W |
| Depth | 50.00 mm | Current type | AC |
| Height | 54.00 mm | Power factor | 0.4 |
| Finish | Clear | Energy efficiency class | E |
| Colour | Silver | Energy consumption | 4 W |
| Colour housing | Silver | Lamp efficacy | 94.59 |
| Body material | Glass | | |
| Lifespan | 15000 hours | | |
| Switches | 30000 | | |
| Beam angle | 36 ° | | |
| Dimmable | Yes | | |
| Degree of protection | IP20 | | |
| Net weight | 0.034 kg | | |
| Warranty | 2 years | | |

| LED | |
|-------------------------|--------|
| Filament LED | No |
| LED type | SMD |
| Dimm type | 3-step |
| Number of leds / sticks | 6 |
| Colour consistency SDCM | SDCM6 |
| Dim to warm | No |
| Adjustable beam angle | No |

| Light | |
|-----------------------------|----------|
| Kelvin | 2700 K |
| Colour temp nr | 827 |
| Stable lumen | 425 lm |
| Lumen 90 cone | 350 lm |
| Luminous intensity | 694.8 cd |
| Color Rendering Index (CRI) | 80 |

| Ordering details | | |
|------------------|----------------|----------------|
| L642763027-1 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739082908 |
| Inner carton | 10 | 18718739082905 |
| Outer carton | 100 | 28718739082902 |

Remark

General note: GU10 glass versions need to cool down after 8 hrs burning (switch off for half an hour), because of limited heat dissipation Dimming levels: Step 1: 100% brightness; step 2: 50% brightness; step 3: 15% brightness.

