





L658928435

LED 2D GR10q 4pin 200x200mm 230V
1680Lm 14W (2D 28W) 3500K 835 130° AC
Opal Niet-Dimbaar

Marine & Industrie, 2D



General		Energy		
Eprel registration no	2271199	Operating voltage	230 V	
Socket	GR10q	Volt	220..240 V	
Width	200.00 mm	Frequency	50..60 Hz	
Depth	30.00 mm	Watt	14 W	
Height	200.00 mm	Current type	AC	
Finish	Opal	Power factor	0.9	
Colour	White	Energy efficiency class	E	
Colour housing	White	Energy consumption	14 W	
Body material	Polycarbonat	Lamp efficacy	120.00	
Lifespan	15000 hours	LED		
Switches	15000	Filament LED	No	
Beam angle	130 °	LED type	SMD	
Dimmable	No	Dimm type	Non-Dim	
Degree of protection	IP20	Number of leds / sticks	60	
Net weight	0.120 kg	Colour consistency SDCM	SDCM6	
Warranty	2 years	Dim to warm	No	
Light		Adjustable beam angle	No	
Kelvin	3500 K	Ordering details		
Colour temp nr	835	L658928435	Quantity pc(s)	EAN
Stable lumen	1680 lm	Single package	1	8718739075139
Color Rendering Index (CRI)	80	Outer carton	10	28718739075133

