

NOCTIS LUX 3

SLI029050NW_CZUJNIK_PW

Floodlight NOCTIS LUX 3, with a power of 30 W. It has a high IP44 rating, making it ideal for use in areas of high humidity. IK07 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Designed for surface mounting.

IP44

IK07



Power **30 W**

Beam angle **100 °**

Degree of protection (IP) **IP44**

Voltage **230 V**

IK **07**

Technical data

Code	SLI029050NW_CZUJNIK_PW
Power	30 W
Nominal current	130 mA
Voltage	230 V
Energy consumption	30 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	2800 lm (120°)
Luminous flux	2800 lm (360°)
Lamp efficacy	93 lm/W
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	20 / +40 °
Warranty	2 years
Lifespan	17000 h
(On/Off)	15000
Housing material	Aluminum, GLASS
IK	07
Degree of protection (IP)	IP44
Colour	Czarny
Dimension (AxBxC)	150x190x53 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC


Logistics data


Bulk packaging	20 pcs.
Quantity per pallet	640 pcs.
Gross weight (1 pcs.)	0.476 kg



*applies to the LED source used

Related documents


 User manual

 Declaration of Conformity

 Photometric file

