

AREA

SLI029088NW_PW

AREA100W/150W/200W NW 230V TYP2 IP66 IK08 452x345x56mm BLACK 5Y WARRANTY



Power **100 / 150 / 200 W**
Colour temperature **4000 K**
Beam angle **155 / 70 °**
Degree of protection (IP) **IP66**

Voltage **230 V**
Colour of light **Neutral white**
IK **08**

Technical data

Code	SLI029088NW_PW
Power	100 / 150 / 200 W
Nominal current	870 mA
Voltage	230 V
Energy consumption	200 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.985000
Useful luminous flux*	35000 lm (360°)
Luminous flux	17000 / 25500 / 33000 lm (360°)
Lamp efficacy	175 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	155 / 70 °
RA	70
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	aluminum
IK	08
Degree of protection (IP)	IP66
Colour	Czarny
Dimension (AxBxC)	452x345x56 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC


Logistics data

Quantity per pallet	56 pcs.
Gross weight (1 pcs.)	4.6 kg


*applies to the LED source used

Related documents



 User manual



 Declaration of Conformity