

WLD+20010_OPAL



Power	20 / 30 / 40 W	Voltage	230 V
Colour temperature	2700 / 4000 / 6000 K	Colour of light	CCT
Beam angle	40 °	Degree of protection (IP)	IP20


Technical data

Code	WLD+20010_OPAL
Power	20 / 30 / 40 W
Nominal current	185 mA
Voltage	230 V
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.950000
Useful luminous flux*	4350 lm (360°)
Luminous flux	1400 / 2000 / 2500 lm (360°)
Lamp efficacy	109 lm/W
Luminous intensity	5900 cd
Colour temperature	2700 / 4000 / 6000 K
Colour of light	CCT
Beam angle	40 °
RA	90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	aluminum
Degree of protection (IP)	IP20
Colour	Czarny
Dimension (AxBxC)	1200x100x25 mm
For use	Inside
Assembly method	On the ceiling, Suspended
Application	Inside
Made in	PRC
Other	Light color change function 2700K / 4000K / 6000K ,

*applies to the LED source used

Related documents



 Declaration of Conformity



 Photometric file

