

WLD+40011_CCT_2F

SYSTEM SHIFT CCT- GRID S LINING FIXTUE 220X23X42 12W 40deg BLACK CCT SWITCH 5YW 2F



Power	12 W	Voltage	48 V
Colour temperature	2700 / 3300 / 4000 K	Colour of light	CCT
Beam angle	35 °	UGR	<19
Degree of protection (IP)	IP20		

Technical data

Logistics data

Code	WLD+40011_CCT_2F
Power	12 W
Nominal current	263 mA
Voltage	48 V
Energy consumption	12 kWh/1000h
Frequency	DC Hz
Protection class	III
Power factor	1
Useful luminous flux*	1200 lm (360°)
Luminous flux	820 lm (360°)
Lamp efficacy	100 lm/W
Luminous intensity	2580 cd
Colour temperature	2700 / 3300 / 4000 K
Colour of light	CCT
Beam angle	35 °
UGR	<19
RA	90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	aluminum
Degree of protection (IP)	IP20
Colour	Czarny
Dimension (AxBxC)	220x23x42 mm
For use	Inside
Assembly method	on track 48V
Made in	PRC
Other	2F ,
Catalogue number	WLD+40011_CCT_2F ,

*applies to the LED source used

Related documents



 Declaration of
Conformity